

Progressive scan CCD camera


Preliminary

KP-F145WCL (Near Infrared Monochrome)




What's WCL

Camera Link



Automatic power supply change.

PoCL



Features

- Extended spectral response allows the use of the camera in the near infrared region.
- The 2/3-inch 1.45M pixels square lattice progressive scan CCD achieves the high resolution of 1392 (H) × 1040 (V).
- The camera has the very compact dimensions of 44(W) × 44(H) × 41(D) mm. (A 26pin SDR connector for digital output makes the camera even compact.)
- Output of 1392(H) × 1040(V) images at 30 frames per second.

Main specifications and functions

	KP-F145WCL
Imaging device	2/3-inch interline CCD
Effective pixels	1432 (H) × 1050 (V)
Pixel size	6.45μm (H) × 6.45μm (V) (square lattice)
Sensitivity	400 lx, F8, 3200 K
Sensing area	8.98mm (H) × 6.71mm (V)
Frame rate	30 frames/second (full pixel readout)
Pixel frequency	57.6000MHz
Video output	Digital output PoCL / non-PoCL (12bit, 10bits or 8bits)
Electronic shutter (Global Shutter)	OFF, 1/30, 1/60, 1/100, 1/250, 1/1000, 1/2000, 1/10000, 1/50000 second. OFF is normal exposure (frame rate) or changeable by variable shutter
Partial scan	Selectable start position and width of picture grabbing in 1H step.
Lens mount	C mount
Power-supply voltage/current consumption	DC12V±1VDC/Approx.230mA (Approx.2.76W)
Ambient Performance	0 to +40°C
External dimensions	44 (W) × 44 (H) × 41 (D) mm (Not including protrusions)
Mass	Approx. 110g

CAUTION : To ensure safe operation, please read the instruction manual before using this product.

These Specifications are subject to change without notice.

Hitachi Kokusai Electric Inc.

Head Office : 14-1, Sotokanda 4-choume, Chiyoda-ku, Tokyo 101-8980, Japan
Phone : (+1)516-921-7200, Fax : (+1)516-496-3718

URL : <http://www.hitachi-kokusai.co.jp/>

Hitachi Kokusai Electric America, Ltd. URL : <http://hitachikokusai.us>

Headquarters and : 150 Crossways Park Drive, Woodbury, New York 11797, U.S.A.

Northeast Office : Phone : (+1)310-328-6116, Fax : (+1)310-328-6252

West Office : 11258 Monarch, Unite Garden Grove, CA 92841

Midwest Sales : Phone : (+1)330-334-4115, Fax : (+1)516-496-3718

Service : (+1)989-345-5379

Hitachi Kokusai Electric Europe GmbH

URL : <http://www.hitachi-keu.com>

Sales and Engineering : Siemensstr. 9, D-63263 Neu-Isenburg, Germany

Frankfurt office : +49(0) 6102-8332-0, Fax : +49(0) 6102-202616

London office : Windsor House, Britannia Road, Waltham Cross,

Hertfordshire EN8 7NX, United Kingdom

Phone : +44(0) 845-121-2177, Fax : +44(0) 845-121-2180

General email address : uksales@hitachi-keu.com

Hitachi Kokusai Electric Canada, Ltd.

URL : <http://hitachikokusai.ca>

Head Office : 1 Select Avenue Unit#11 Scarborough, Ontario M1V5J3, Canada

Phone : (+1)416-299-5900, Fax : (+1)416-299-0450

Eastern Office : 5795 Chemin St. Francois St. Laurent, Quebec H4S 1B6, Canada

Phone : (+1)514-332-6687, Fax : (+1)514-335-1664

Hitachi Kokusai Electric (Shanghai) Co., Ltd.



CERTIFICATE No.

JMI-0062

ISO 9001/BS 5750Pt1